


TECHNICAL DATA

O.RING	EPDM
SLIPPER	PTFE+CARBON FIBER
BUSHING	AISI 316
NOZZLES POSITIONS	2 - 4
NOZZLES SIZE	1/8"G SPECIAL
MAX OPERATING FLOW	100 L/min
MAX OPERATING PRESSURE	200 bar
MIN PASS THROUGH HOLE	74 mm ON CENTER LINE
MAX TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
GEARS	FIXED Z=23 ROTATING Z=59
MODULE	1
FULL CYCLE	59 ROTATIONS
FULL CYCLE TIME	3.5 MIN.
ELECTRIC MOTOR	BB0015
ELECTRIC MOTOR VOLTS	24V AC/DC
ELECTRIC MOTOR AMPS	0.30 A
ROTATION SPEED	17 RPM
WEIGHT	7.5 KG

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
FOGLIO	XXXX						
GREZZO	DATA	XX.XX.XX					DISEGN.: CR CONTR.: DM DATA: 04.06.12 MOD. SCALA
~ = ✓	TOLLERANZE GENERALI classe m UNI-EN 22768/1						
SGROSS.	0÷6	6÷30	30÷120	120÷400	400÷1000	1000÷2000	1:4 A4 0
∇ = 3.2/∇	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	
FINITURA	MATERIALE: INOX						DESCRIZIONE: XB 100 EEB cm INSTALLATION DRAWING CODICE: XB 100 EEB
∇∇ = 1.6/∇							
RETTIFICA							
∇∇∇ = 0.8/∇							